

Wirefeed Unit CM-0401-D

The CM-0401-D wire feed unit is a component that has been specially developed for ARXIS welding power sources.

The CM-0401-D wire feed unit is a component that has been specially developed for ARXIS welding power sources. It enables precise and controlled feeding of the welding wire during the welding process. This unit ensures a reliable wire feed speed and thus contributes to uniform and high-quality weld seam formation.

Specification

| | |
|-----------------------------------------------|-----------------------------------------------------------|
| Type | CM-0401-D |
| Anwendbarer Drahtdurchmesser | Ø 0.6, - 2.4 mm |
| Werkseitige Einstellung des Kabelquerschnitts | Ø1.2 mm |
| Drahtvorschubgeschwindigkeit | 1.5 – 22 m/min |
| Stromversorgung | DC 42 V |
| Motorstrom | 2.5 A |
| Brenneranschluss | EURO |
| Gewicht des zu verwendenden Drahtes | Max. 25 kg |
| Schutzgas (maximaler Druck) | CO ₂ , Ar, ArCO ₂ mixture (0.4 MPa) |
| Art der Kühlung (maximaler Druck) | water, water/glycol mixture (0.5 MPa) |
| Maximal zulässige Belastung | 500 A(60%) / 430 A (100%) |
| Gehäuseklasse | IP23 |
| Konformität Standard | IEC 60974-5 |
| Temperaturbereich | 10 ~ 40 °C |
| Feuchtigkeitsbereich | 20 ~ 80% (no condensation) |
| Temperaturbereich bei Lagerung | -10 ~ 60 °C |
| Bereich der Lagerfeuchtigkeit | 20 ~ 80% (no condensation) |
| Äußere Abmessungen (BxTxH) | 317 mm x 775 mm x 392 mm |
| Gewicht | 16 kg |



Product information

Order No. 254000018

Model No. 0